Antenna Installation

1. Antenna placing



3G/4G Antenna mounted upright on metal surface



3G/4G Antenna mounted upright on non-metal surface



3G/4G Antenna is horizontal



WiFi antenna is mounted upright




WiFi antenna is mounted horizontally

Note:


- 1. Please connect the antenna before energizing the router to avoid impedance mismatching which may result in poor signal.
- 2. Connect the 10dBi network antenna (the one with magnetic base) to **Main 3G/4G** interface while the Wifi antennas to **AUX/WiFi** interface port. Wrong connection will result in poor signal
- 3. Please until the cable of antenna, otherwise the signal will be influenced.



2. High gain antenna (10dBi) install











- 1. Screw on the lower antenna section to the antenna base.
- 2. Place the upper antenna section onto the lower antenna section.


Ensure the screw lines up with the flat surface of the lower section.

- 3. Screw and tighten the upper antenna section to the top of the lower section.
- 4. Check the upper section is secured tightly by pulling gently upwards. You have now successfully setup the antenna and ready to connect.


Note: You will need a 2mm hex key



SIM Card Installation









- 1. Please **do not** power up the router before installing the Sim Card
- 2. On the side of the router, remove the screw to open the Sim card slot cover *Ensure the right size of the screwdriver is used*
- 3. Insert the Sim Card with correct SIM card direction

 Ensure the Sim Card insert position matches the illustrated Sim Card profile shown at the bottom of the slot.
 - Ensure the Sim Card is pushed to the end. Standard Size Sim Card is required.
- 4. Reinstall the SIM card cover in order to protect the SIM card during router operation

Note: You will need a #0 OR #1 Cross Screwdriver